



**CUSHMAN®**

# HAULER® 1200



## **BUILT TO HANDLE THE BIG JOBS.**

The Cushman® Hauler® 1200 is built to take on the chores that smaller vehicles hide from. With a powerful but fuel-efficient 13.5 hp Kawasaki® engine, a 9.6-cubic-foot cargo bed and a total capacity of 1,200 pounds, this machine tears through tough tasks. When your job site needs a big job done fast, you need the Hauler 1200.

**LET'S WORK.®**

**1200LB**  
TOTAL LOAD  
CAPACITY

**9.6CU FT**  
CARGO BED  
CAPACITY

**LIMITED**  
SLIP  
DIFFERENTIAL  
OPTION



# CUSHMAN® HAULER® 1200



HEADLIGHTS



OPTIONAL REAR  
HITCH RECEIVER

ROTO-MOLDED CARGO BED

## OPTIONS & ACCESSORIES

- Differential Guard
- Locking Glove Box
- Windshield
- Canopy
- Aluminum Bed
- Taillights
- Roll Over Protection System with Seat Belts and Side Nets
- Brakelights
- Trailer Dump (Steel and Poly)
- Body Color (Ivory, Bright White, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

### BODY & CHASSIS

FRAME	DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)
STANDARD COLOR	Forest Green

### DIMENSIONS

OVERALL LENGTH	113.0 in (287 cm)
OVERALL WIDTH	49.5 in (126 cm)
OVERALL HEIGHT	46.5 in (118 cm) (w/o Roof) / 70.0 in (178 cm) (w/ Struts & Roof)
WHEEL BASE	77.0 in (196 cm)
WHEEL TRACK	37.0 in (94 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm)
CARGO DECK CAPACITY	9.6 cu ft (0.27 m³)
CARGO DECK MATERIAL	Roto-Molded Polyethylene

### POWER

POWER SOURCE	4-Cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal
AIR CLEANER	Replaceable Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6.0 Gallon (22.7 L) Tank
DRIVE TRAIN	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Forward - Reverse
REAR AXLE RATIO	11.42:1 (Forward) 15.78:1 (Reverse)

### PERFORMANCE

SEATING CAPACITY	2-Person (Bench)
CURB WEIGHT	978 lb (443 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
BED LOAD CAPACITY	800 lb (363 kg)
TOWING CAPACITY	720 lb (360 kg) Max Load
SPEED	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	Links 18 x 8.5 - 8 (4 Ply Rated) (Front) / Turf Saver 20 x 10.0 - 8 (Rear)

[www.cushman.com](http://www.cushman.com)

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82290-G4 (Rev. 01/2016)